


C.O. NO. REV. REVISION DESCRIPTION
ASC4405 D SEE SHEET 1 FOR REVISIONS



-7 SCHEMATIC

SPACE CONTROL
WICHITA, KANSAS
P/N
S/N

ø.205/.200 THRU −(2 PLCS.)

-3/16" HIGH MACHINED IMPRESSION

ELECPAC HERMTIC RECEPTACLE PART No. 90710-082 - OR PART No. 90710-086 (REF. MIL-C-5015, MS33678-105L-4P)

DECAL IS DISPLAYING NOTATION AS APPLICABLE ON SAME BUT OUT OF ACTUAL POSITION FOR DETAILING PURPOSES


..... 85

Ξ

d

4

| 89 1.38



-7 ASSEMBLY

NOTES: UNLESS OTHERWISE NOTED

- 7. APPLICABLE TO SHEET (1)
- APPLICABLE TO SHEET (1)
- 9. CONTINUOUS DUTY CYCLE
- 10. OPERATING CURRENT: .40 AMPS MAXIMUM AT 28VDC AND 70°F
- 11. OPERATING PRESSURE: 0 TO 16 PSIG

12. MINIMUM FLOW AT 70F: 3.20 LBS./MINUTE AT 16 PSID

- 14. VALVE CLOSED POSITION LEAKAGE: 0, (3 BUBBLES MAXIMUM IN 30 SECONDS) WITH 10 PSID APPLIED IN FLOW DIRECTION.
- 13. VALVE POSITION: NORMALLY CLOSED
- 16. BURST PRESSURE: 45 PSIG AT INLET PORT FOR (5) MINUTES WITH NO EVIDENCE OF RUPTURE OR EXCESSIVE LEAKAGE.

15. PROOF PRESSURE: 37.5 PSIG AT INLET PORT FOR (2) MINUTES WITH NO DEFORMATION OR MALFUNCTION.

17. SEE DRAWING 4009101 FOR APPLICABLE ASSEMBLY DETAILING FOR EACH CONFIGURATION

